

## COMPACT AI Vehicle Series

Computer Vision Edge Unit with NVIDIA Jetson AGX Xavier

LTE / GNSS / Wi-Fi



Dual nanoSIM  
CFast  
microSD



DC supply

2x CAN

4x PoE LAN  
RJ45

2x LAN  
M12 x-coded

2x USB 3.1

DP

## IPC/COMPACT A3 - RML

This fanless RML COMPACT-A3 generation is based on the Jetson AGX Xavier processor module and offers a wide range of interface options.

The robust and uncompromising industrial design allows the implementation in the most demanding mobile AI applications and guarantees long term availability.

- Power over Ethernet (PoE+), 48VDC out
- 24/7 continuous operation
- Extended AI Computing
- Passively cooled, no moving parts
- Long term availability with fixed BOM



Linux for Tegra (L4T)



### Product Highlights

UNECE-R10 (E-mark) certified  
Power ignition controller  
Each LAN interface has its own dedicated NIC  
Shock and vibration resistant  
LTE and Wi-Fi connectivity options  
No moving parts / passively cooled

### Product Features

512-Core NVIDIA Volta™ GPU  
with 64 Tensor Cores  
8-Core ARM v8.2 64-bit NVIDIA Carmel CPU  
32GB 256-Bit LPDDR4x RAM soldered on board  
Storage options: NVMe M.2 2280 & CFast  
Ethernet, USB, CAN (J1939)  
LTE, GNSS and WiFi  
Aluminum & stainless steel housing

### Industries

Automotive  
Autonomous Mobile Robots (AMRs)  
Transportation  
Robotics  
Off-highway vehicles

Processor module / Performance		
NVIDIA Jetson AGX Xavier (32GB)   512-Core NVIDIA Volta™ GPU with 64 Tensor Cores		
8-Core ARM v8.2 64-bit NVIDIA Carmel CPU		
AI Performance	32 TOPs	32 TOPs
Memory / Storage		
Data L3 Cache Size	4MB	4MB
256-Bit LPDDR4x RAM soldered on board	32GB	32GB
eMMC 5.1 Flash Storage on board	32GB	32GB
microSD Card socket	1	1
M.2 2280 Key M socket (for NVMe SSD) <sup>2</sup>	1	1
CFast socket with retention frame <sup>2</sup>	1	1
Features		
Inertial measurement unit (IMU) STMicroelectronics ISM330DHCXTR	on request	on request
Real time clock (RTC) with battery backup Renata CR2477 (950 mAh)	•	•
Communication Interfaces		
Graphic interface	DisplayPort 1.2	DisplayPort 1.2
USB version 3.1 (10 Gbit/s) (Type A)	2	2
Internal USB version 2.0 OTG <small>behind the cover</small> (micro USB Type AB)	1	1
Ethernet 10/100/1000 BASE-T (M12 female x-coded)	2	2
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated (DSUB9)	2	2
Power over Ethernet - IEEE802.3at 10/100/1000Mbit (RJ45)	4	4
PSE - Power sourcing equipment, producing 48VDC out	(total max power: 39W)	(total max power: 39W)
Serial RS232 / RS422/RS485 (DSUB9)	on request	none
Digital I/O's, 24VDC (up to 4 inputs & 4 outputs)	on request	none
Analog input, 16bit resolution, voltage input: -10 ...+10V / 0 ... 30V Accuracy: +/- 0.1% (4 inputs)	on request	none
Analog input, 16bit resolution, current: 0-20mA (4 inputs)	on request	none
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface <sup>1</sup>	on request	on request
Wireless Connectivity		
Cellular 4G Module (LTE/UMTS/GSM) with built-in GNSS Telit LE910C4-WWX <sup>6</sup> (Dual nano SIM support)	3x SMA	none
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 5.0 Emwicon WMX6218 <sup>6</sup>	2x RP-SMA	none
High Accuracy GNSS Positioning Module w/ RTK & optional heading support <sup>1</sup> u-blox ZED F9R / F9P	on request	none
Technical Data		
Dimensions [mm] (housing, incl. mounting plate)	w256 x h95 x d127	w256 x h95 x d127
Net weight [gram]	~2800	~2750
Non isolated input voltage with ignition controller and reverse polarity protection (M12 5P male a-coded)	9 ... 45VDC	9 ... 45VDC
Power consumption <sup>3</sup>	depends on power mode (15W, 30W, MAXN)	
Environmental Conditions		
Operating temperature <sup>3</sup>	-25°C ... +60°C	-25°C ... +60°C
Storage temperature	-25°C ... +80°C	-25°C ... +80°C
Ingress protection standard according to EN60529 (ISO 20653)	IP20	IP20
Conformal coating <sup>4</sup>	on request	on request
Road vehicles UNECE-R10 (E-mark) <sup>5</sup>	on request	on request
Shock	EN60068-2-27	EN60068-2-27
Vibration	EN60068-2-64	EN60068-2-64
EMI-Conformity	EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)	EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)	RED	RED
MTBF @ 25°C ambient <small>according to Telcordia SR-332, Environment GB, excluding battery</small>	~280 000h	~355 000h

<sup>1</sup>Please contact factory for minimum order quantities

<sup>2</sup>Internal connector

<sup>3</sup>Depending on installation situation, interface connection and power mode. Please see user documentation.

<sup>4</sup>On all possible components (excl. NVIDIA Xavier Module, connectors and wireless devices)

<sup>5</sup>UN/ECE-R10 is the type-approval test for European automotive electronics. It includes a variety of testing including RF immunity and emissions, transient immunity and emissions.

<sup>6</sup>These LTE and Wi-Fi modules have replaced the previously used Sierra Wireless MC7455 and SparkLAN WPEB-263ACNI(BT) due to these modules going EOL (previous products: IPC/RMLA3K22-B203S)

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2023 Syslogik Datentechnik AG  
All rights reserved

Syslogik Datentechnik AG  
Täferstrasse 28  
CH-5405 Baden Dättwil

Version 2.0 | January 2023

For further information and support:  
info@syslogik.com  
support@syslogik.com  
www.syslogik.com

+41 56 200 90 40 Switzerland (Headquarters)  
+49 7741 9671-420 Germany and Austria

 **syslogik**  
industrial computing