

COMPACT AI Rugged Series

Intelligent Machine Learning Unit with NVIDIA Jetson TX2 NX

preliminary

Rugged AI Computer

optional
LTE / GPS / Wi-Fi



2x USB 2.0
microSD
DisplayPort

Image similar

Power Supply
9 ... 45VDC

CAN

2x Gbit LAN

USB 3.1

HDMI

RPC/COMPACT A2N

This fanless COMPACT A2N generation is based on the NVIDIA Jetson TX2 NX processor module and offers a wide range of interface options.

The robust and uncompromising industrial design allows the implementation in the most demanding AI applications and guarantees long term availability.

- 24/7 continuous operation
- Extended AI Computing
- IP67 protection
- Product lifecycle management
- Long term availability with fixed BOM

 **NVIDIA.** Linux for Tegra (L4T)

Product Highlights

- Ultra rugged
- Sealed housing
- Shock and vibration resistant
- Maintenance free
- No moving parts / passively cooled
- Hardware watchdog
- Temperature supervision
- Long term availability (fixed BOM)

Product Features

- 256-core NVIDIA Pascal™ GPU Dual-Core
- NVIDIA Denver 2 64-Bit CPU Quad-Core
- ARM® Cortex®-A57 MPCore
- 4GB 128-bit LPDDR4x RAM soldered on board
- M.2 slot for storage
- Ethernet, USB, active / passive CAN
- Optional LTE & WiFi extensions
- Aluminum housing
- Ingress Protection class IP67

Markets / Applications

- Automated Guided Vehicles (AGV)
- Agriculture
- Automotive
- Transportation
- Construction Vehicles
- Cleantech
- Outdoor applications



Processor module / Performance		
NVIDIA Jetson TX2 NX 256-core NVIDIA Pascal™ GPU	•	•
6-Core ARM CPU (Dual-Core NVIDIA Denver 2 64-Bit CPU and Quad-Core ARM® Cortex®-A57 MPCore)	•	•
AI Performance	1.33 TFLOPs	1.33 TFLOPs
Memory / Storage		
Data Cache Size	2MB	2MB
128-bit LPDDR4 RAM soldered on board	4GB	4GB
eMMC 5.1 Flash Storage on board	16GB	16GB
M.2 2280 slot for SSD storage up to 2TB ²	1	1
microSD card socket ²	1	1
Features		
Inertial measurement unit (IMU) STMicroelectronics ISM330DHCXTR	•	•
Real time clock (RTC) with battery backup Renata CR2477N (950mAh)	•	•
Hardware Watchdog & Temperature supervisor	•	•
Communication Interfaces		
Graphic interface <small>behind the service cover</small>	DisplayPort 1.4	DisplayPort 1.4
Internal USB version 2.0 OTG <small>behind the service cover</small> (micro USB Type AB)	1	1
USB version 2.0 <small>behind the service cover</small> (Type A)	2	2
Graphic interface	HDMI 2.0	HDMI 2.0
USB version 3.1 (Type A)	1	1
USB version 2.0 ¹ (Type A)	optional	optional
Ethernet 10/100/1000Mbit (1x native, 1x I210-IT)	(M12 female, x-coded)	2
Active/passive-CAN ESD protected, isolated	(M12 female, a-coded)	1
Serial RS232 ²	2	2
Mini PCIe socket ²	2	2
I2C bus ²	1	1
Buzzer	1	1
MIPI CSI-2 / GMSL2 / FPDLinkIII Camera interface ¹	on request	on request
Wireless Connectivity		
Cellular Module (LTE/UMTS/GSM) with GNSS positioning functionality Sierra Wireless MC7455 - M2M only! (Dual nano SIM)	none	3x SMA
Wireless LAN IEEE 802.11a/b/g/n/ac dual-band 2x2 MIMO & Bluetooth 4.1 SparkLAN WPEB-263ACNI(BT)	none	2x RP-SMA
High precision GNSS module ¹ u-blox ZED-F9P module	optional	optional
Technical Data		
Dimensions [mm] (housing, incl. mounting)	w245 x h75 x d165	w245 x h75 x d165
Net weight [gram]	~2000	~2000
Non isolated Input voltage, with Ignition controller, reverse polarity protected (M12 male, a-coded)	9 ... 45VDC	9 ... 45VDC
Idle power consumption typ. in Watt @ 24V without Add-Ins	~10	~10
Environmental Conditions		
Operating temperature ³	-25°C ... +70°C	-25°C ... +70°C
Storage temperature	-25°C ... +85°C	-25°C ... +85°C
Ingress protection standard according to EN60529	IP67	IP67
Conformal coating ⁴	on request	on request
Shock (designed to meet)	EN60068-2-27	EN60068-2-27
Vibration (designed to meet)	EN60068-2-64	EN60068-2-64
EMI-Conformity (designed to meet)	EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)	EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)	RED	RED
estimated MTBF @ 25°C ambient <small>excluding battery</small>	tbd	tbd

¹ Please contact factory for minimum order quantities

² Internal connector

³ Depending on installation situation and interface connection. Please see user documentation

⁴ On all possible components (excl. Xavier NX module, connectors and wireless devices)

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.

© 2021 Syslogik Datentechnik AG
All rights reserved

Syslogik Datentechnik AG
Täferstrasse 28
CH-5405 Baden Dättwil

Version 0.1 | March 2021

For further information and support:
info@syslogik.com
support@syslogik.com
www.syslogik.com

+41 56 200 90 40
+49 7741 9671-420

Switzerland (Headquarters)
Germany and Austria

 **syslogik**
industrial computing